

## PREMIUM POWER

PRODUCTS

# 3rd Generation Internal Battery For iPod®

The instructions below come with no warranty or guarantee. Improper assembly or use of excessive force may result in damage to your iPod®. The buyer assumes full responsibility for damages or problems caused by use of these instructions. Installing this battery requires a moderate level of technical ability and proficiency in the use of hand tools as well as a general understanding of electronic components.



#### Step

Measure 6cm (2-3/8") down one side of the iPod® and begin prying the case open at this point. Work back and forth along the seam using the included, 4-way multi-screwdriver.



### Step 2

Carefully loosen one side first, then work your way around the iPod®, undoing the clips from the silver case by prying towards the center of the iPod®. The case will still be attached by a ribbon cable—do not detach the ribbon cable.



### Step:

Once the case is open, remove the hard drive by carefully lifting the blue rubber padding with the hard drive away from the iPod®. The hard drive will be connected at the base by a small ribbon cable tab. Gently lift this tab, disconnect the hard drive and set it aside for re-assembly.



### Sten

Use the included tool to remove the battery from its compartment. You will notice the power cable is wrapped under the green motherboard. Carefully pull the power cord out from under the motherboard and unplug the power connector to remove the battery.



### Step !

Plug in the new battery, making sure to wrap the power cord back under the motherboard before securing the battery to its compartment. Reconnect the hard drive to the motherboard and verify the connection by gently pulling on the hard drive. Secure the hard drive back into position and snap the silver metal case back on the iPod®.

Your new battery will need a minimum of three hours charge time before its first use.

iPod® is a trademark of Apple Computer Inc.